



Truck Clutch & Flywheel Handlers

BEST

Truck Clutch and Flywheel Handler – Low Clearance

- Open stance for ease of access to the work. Unique, patented linkage design raises the load from horizontal to vertical as the pump is cycled. This eliminates any lifting of the clutch by the operator.
- Handles 14" and 15-1/2" clutch assemblies weighing up to 250 lbs. Swivel casters provide easy maneuverability. Includes a 2" splined shaft with a 1-1/4" pilot to aid in alignment.
- 360° swivel head.
- Minimum height of 15" allows access below side faring.
- When raised, center line of clutch will be 38-1/4" off floor.
- Floor space is 32-3/8" long by 24-1/2" at widest point.
- Makes the task an easy, one-person job.

No. 5018A – Truck clutch handler – low clearance. Wt., 125 lbs.

Optional Accessories:

No. 516160 – Flywheel handling attachment for use on No. 5018/5018A only. Wt., 5 lbs., 11 oz.

No. 515686 – Splined shaft, 1-3/4" dia. with 1-1/4" pilot. Wt., 5 lbs., 7 oz.

No. 516159 – Splined shaft, 1-3/4" dia. with 1" pilot. Needed for clutch service on some Navistar 466 series engines. Wt., 5 lbs., 7 oz.



5018A



Truck Clutch and Flywheel Handler

- Handles 14" and 15-1/2" clutch assemblies weighing up to 150 lbs. Lifting range of 9" to 37". Swivel casters provide easy maneuverability. Includes a 2" spline shaft with a 1-1/4" pilot to aid in alignment.
- Makes the task an easy, one-person job.
- Covered by OTC Lifetime Marathon Warranty®.

No. 5015A – Clutch and flywheel handler. Wt., 95 lbs., 3 oz.

Optional Accessories:

No. 218174 – Flywheel handling attachment for use on No. 5015/5015A only. Wt., 5 lbs., 13 oz.


No. 48625 – Optional splined shaft, 1-3/4" dia. with a 1-1/4" pilot. Wt., 5 lbs., 7 oz.

No. 440533 – Optional splined shaft, 1-3/4" dia. with a 1" pilot. Needed for clutch service on some Navistar 466 series engines. Wt., 5 lbs., 7 oz.

No. 314386 – Optional 1-3/4" dia. alignment shaft extension. Used for 2-plate clutch of Navistar 466 series engine. Wt., 2 lbs., 12 oz.



5015A



218174



314386

BETTER

09-45 ©2009 SPX, All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Product shipped may differ from photo(s) shown.



800-533-6127

www.otctools.com

